

**26AC4031**

**Load break switch SIRCO AC 4P 315A 690 VAC Front operation**



SIRCO AC are manually operated multipolar load break switches. They make and break under load conditions and provide safety isolation. SIRCO AC are designed for harsh applications up to 1000 VAC - AC 23

**Strong points**

- Reliability and performance
- Safety of property and personnel
- Simplicity
- Easy to install

**General characteristics**

- Double positive break indication given through a position indication window, located directly on the product, and by the operating handle.
- Severe load duty categories (AC-22 and AC-23).
- High resistance to damp heat (supplied 'tropicalised')

**Compliance with standards**

- IEC 60947-3

**Link to the reference**



<https://emea.socomec.com/en/reference/26AC4031>

**Classification**

UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290

**Commerce**

Description	Manually operated Load break switch SIRCO AC frame B4b with 4 poles, 315A, 690 VAC frontal direct operation with handle type J1 or frontal external operation with handle type S2. Delivered without handle
Effective date	2012-07-03
Offer Life Cycle Code	40
Country of origin	FR

**Environmental Sustainability**

Climate change - Total - Cradle to Grave [kg CO <sub>2</sub> eq.]	223
Climate change - Total - Cradle to Gate [kg CO <sub>2</sub> eq.]	15
SVHC > 0.1 mass percentage?	No
RoHS applicable?	Yes

**ETIM - Electrical characteristics**

Max. rated operation voltage Ue AC [V]	690
Rated operating voltage [V]	400..690
Rated permanent current Iu [A]	315
Rated permanent current at AC-23, 400 V [A]	315
Rated permanent current at AC-21, 400 V [A]	315
Rated short-time withstand current Icw [kA]	8
Rated operation power at AC-23, 400 V [kW]	160
Switching power at 400 V [kW]	160
Conditioned rated short-circuit current Iq [kA]	50
Number of poles	4

**ETIM - Mechanical characteristics**

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20
Width [mm]	230
Height [mm]	160
Depth [mm]	115

### ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

### Logistics

GTIN/EAN	3596032774493
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	2.366
Length of the packing unit [m]	0.113
Width of the packing unit [m]	0.185
Depth of the packing unit [m]	0.238

### Norms

Conformity to standards	IEC
-------------------------	-----

### Technical Characteristics

Height [mm]	160
Width [mm]	230
Depth [mm]	115
Weight [kg]	2.366
Control operator	Direct : B2, J1 / External : S2
Number of poles	4
Rated voltage	690 VAC
Rated current [A]	315
Type	Front operation
Frame size	B4b